Installation Instructions

NOTE:

mCAR.UMI replaces the CD Changer in the MOST network. After the installation the CD changer optical connection will not be connected anymore.

Step 1

First remove the head unit display to allow access to the CD changer unit. Remove all electrical connectors and slide out the navigation screen to allow easy access to the back.






Step 2

On the CD Changer harness lift the lock tab gently and pull the insert out of the housing.

Step 3

Take the mCAR.UMI connector housing from the kit and plug back the inserts with the leads into the mCAR.UMI connector.




Step 4

Crimp the black wire to ground and the red wire to 12V Battery Power off the CD changer harness.


Step 5

Remove the white optical dust protector from mCAR.UMI optical connector and insert it into the CD Changer optical MOST connector to protect from dust and contaminations.



Step 6

Connect the MOST and the Power plugs to the rear mCAR.UMI panel.



Step 7

Connect the USB and the microphone plugs to the front panel of the mCAR.UMI.

Step 8

Pull the decorative edge and wire the microphone from the mCAR.UMI to the right side of the dash panel.

Note: avoid installing the microphone in the dash cavity to prevent eco effects.



Step 9

Install mCAR.UMI behind the navigation screen horizontally and slide the screen back to its position. Be sure that no wires stand in between.

Step 10

Secure the navigation screen, the decorative edge and the CD Changer in their original positions. Plug back all electrical connectors to power the CD Changer panel.

Step 11

Install the USB receptacle to extend to the glove box or the ash tray using the grommet included in the kit.




Step 12

You may also use the special USB grommet for panel installation as shown.

Step 13

Insert the ashtray back and lock it to its original position. Now you can power the head unit and follow the User Guide for operation instructions. You will find the mCAR.UMI at the CDC menu and the Bluetooth hands free and A2DP at the TEL menu.



mCAR.UMI module 2+4 MOST Harness MOST inline connector Power Supply Harness **USB Extension Cable** Cigarette lighter grommet Microphone w/ 2.5mm jack Velcro/Adhesive Pad

TQ6BTMDC751

Installation Kit includes

Weight: 350g Size: 6" x 9" x 2"

mCAR Product References

This device contains FCC ID TQ6BTMDC751